## INFIELD

## MILOR





## Soft foam adaptor ensures higher safety when worn

The soft foam adaptor ensures perfect safety for the eye area in every working situation. Also the face is protected against injuries in frontal impacts.



| 35 g       | GA 166 F CE          | Polycarbonat  | e 100%   | <b>10 pcs</b> .  | Easy Fit Sof  | t   |
|------------|----------------------|---|--|--|---|---|
| Weight     | Code – version       | Lens material   | UV protection  | Packing unit   | Temple technology   | /   |
| Quick Info |                      |   |  |  |   |   |
|            |                      | ~ /0  | ,  |  | configuration or branding with colour   |   |
|            |                      | 0   |  |  |   |   |
|            |                      | 0   |  |  |   |   |
|            | Weight<br>Quick Info | Weight Code - version   Quick Info   ip ensures comfort when worn   lually adjustable safety lens angle | Weight   Code - version   Lens material     Quick Info   Image: Comparison of the second se | Weight   Code - version   Lens material   UV protection     Quick Info   Code - version   Code - version   Very good eye cover     ip ensures comfort when worn   Code - version   Code - version   Code - version     lually adjustable safety lens angle   Non-slip temple   Code - version   Code - version | Weight   Code - version   Lens material   UV protection   Packing unit     Quick Info   Code - version   Code - version   Code - version   Packing unit     Image: Second s | Weight   Code - version   Lens material   UV protection   Packing unit   Temple technology     Quick Info   Code - version   Code - version <th< td=""></th<> |

| Fig.       | FRAME PI  | LENS PROPERTIES |             |    |    |       | MILOR       |              |             |  |  |
|------------|---|-----------------|-------------|----|----|-------|-------------|--------------|-------------|--|--|
| no.        | frame colour(s)   |                 | coating(s)* |    |    |       | code(s) art |              | article no. |  |  |
| [1]        | Blue  | Grey            |             | AF | AS | Clear |             | GA 1 F N CE  | 9232 155    |  |  |
| [2]        | Blue  | Grey            | HC          | AF | AS | Clear |             | GA 1 F KN CE | 9232 006    |  |  |
| * Coatings | * Coatings: HC = scratch-resistant   AF AS = anti-fog, antistatic, scratch-resistant   HC AF AS = scratch-resistant, anti-fog, antistatic   SAR super anti-reflex |                 |             |    |    |       |             |              |             |  |  |